

DC FAST CE 1280kW

SPECIFICATIONS

Up to 96.3%

efficiency @half load rate

Max. 600A output

Output boost to 600A
Continuous charging at 500A

1280kW output

Available for MCS upgrade
Up to 1000kW on one dispenser

User-friendly


Barrier free
Multiple payment methods
More than 15 languages supported

Full certification

CE Eichrecht OCA1.6 RED RCM

Flexible configuration

16 connectors in maximum
Dual-connector dispenser and
wallbox dispenser
available at the same time



Eichrecht Certified



	Item	Parameter
	Electric specification	
Power bank	Rated output power	960kW, 1280kW
	Input Voltage Range	400(±10%) @ 50 Hz
	DC Output Voltage	200-1000V
	Power Factor	≥0.99
	THDI	≤5 %
	Peak Efficiency	96.5%
	Maximum Output quantity	16 connectors
	Protection	Lightning protection
		Emergency protection
		Overload protection
		Short - circuit protection
		Leakage protection
		Overcharge protection
		Over/Under voltage protection
		Reverse connection protection
		Over temperature protection
	Environment specification	
	Operational altitude	<2000 m
	Operating temperature	-25 °C to +50 °C (Full power)
	Humidity	5 %-95 % Rh non-condensing
	Mechanical Specification	
	IP/IK degree	IP55/IK10
	Dimension	W2300*D1100*H2100 mm
	Weight	≤2000kg
	Certificate	
	Certificate	CE, RCM
Dispenser	Electric specification	
	Output voltage	200~ 1000V
	Rated output power	Up to 1000kW
	Maximum current per connector	CCS2(Conventional cooling): 350A(boost to 500A);
	Connector combination	CCS2(Liquid cooling): 500A(boost to 600A); 350A+350A; 500A+500A; 500A+350A
	User interface	
	Cable length	5m /7m (optional)
	Screen	15" HD touchscreen
	User Authentication	Credit Card, QR Code, RFID Card, Autocharge
	Connectivity	Ethernet/GSM, 4G
	Language	English (Support customizing other languages)
	Barrier free design	Yes
	Mechanical Specification	
	Size	W450*D800*H2100 mm
	Protection Level	IP55/IK10
	Weight	≤270kg
	Protocol and standards	
	Backend communication	OCPP 1.6 J(OCPP 2.0.1 available in 2025)
	EV communication	DIN70121, ISO 15118
	Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2
	Certificate	
	Certificate	CE, RCM, Eichrecht, MID compliant, OCA1.6J
Suspended Dispenser	Electric specification	
	Output voltage	200~ 1000V
	Rated output power	Up to 200kW
	Maximum current per connector	CCS2(Conventional cooling): 200A
	User interface	
	Cable length	5m /7m (optional)
	User Authentication	RFID Card, Autocharge
	Connectivity	Ethernet/GSM, 4G
	Mechanical Specification	
	Size	W500*D200*H800 mm
	Protection Level	IP55/IK10
	Weight	≤50kg
	Protocol and standards	
	Backend communication	OCPP 1.6 J(OCPP 2.0.1 available in 2025)
	EV communication	DIN70121, ISO 15118
	Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2
	Certificate	
	Certificate	CE