SINEXCEL

Everything about profitability and charging experience

SEC 80kW Series DC Fast Charger





Overview

The SEC 80kW is an integrated DC fast charger that features high efficiency and flexible configured. It supports the multiple connector charging at the same time and adopts compact design, with a smaller area covered.


The Charger used in centralized fast charging station, it adopts 20kW charging power module of Sinexcel, and meet the charging demand of larger capacity and high endurance electric on the market.


Dimensions





W850*D500*H2030mm





Specifications

80kW Integrated Charger			
	Input voltage	400 VAC +/- 10%	
Input Characteristic	Input frequency	50 Hz/ 60 Hz	
	Input type	3P + N + PE	
	Max input current	150A	
	Max input power	89kVA	
	Power factor	0.99	
	THDi	<5%	
	Grounding type	TN-S, TT	
	Connector options	CCS2	
		CCS2+CCS2	
		CCS2+CHA	
	Output voltage	CCS2: 200-1000 Vdc	
Outout		CHAdeMO: 200-500 Vdc	
Output		300~1000V is the output voltage range of constant power	
Characteristic		output.	
	Maximum output current	CCS2: 200A	
		CHAdeMO: 125A	
	Rated power	DC: 80kW	
	Peak efficiency	96%	
Environment	Operational altitude	<2000 m	
	Operating temperature	-25 °C to +65 °C (Derating operation over 50 °C)	
	Storage temperature range	-30 °C to +70 °C	
	Humidity	5 %-95 % Rh non-condensing	
Structure	IP and IK rating	IP55/ IK10	
	Dimensions	W850*D500*H2030mm	
	Weight	≤350 kg	
Components	Cable length	5 m	
	Screen	15" HD high-contrast touchscreen	
	RFID Reader	ISO 14443 A + B to part 4 and ISO/IEC 15693, Mifare1, NFC	
	Emergency button	Yes	
	Communication interface	4G / LAN Port	
	Language	English (Support customizing other languages)	
	Communication protocol	OCPP1.6J	
	Cooling method	Air cooled	
Others	Payment method	RFID / APP	
		(Mobile phone / Visa / Master is optional)	
	EMC	Class A (industrial)	
	Protection	Undervoltage protection, Overvoltage protection, DC	
		Overcurrent protection, Over-temperature protection,	

		Surge Protection Device, Emergency Stop Protection
	Barrier free design	Yes
	Optional functions	Cable management, tilt detection, flood detection, smoke detection
Standards and	Standards	IEC 61851, IEC 62196, DIN 70121, ISO 15118
Certifications	Certifications	CE, TUV

Shenzhen Sinexcel Electric Co.,Ltd. https://en.sinexcel.com/

Address: 6th Building, 2nd District, Baiwangxin High-tech Industry Park, Songbai Road, Nanshan District, Shenzhen.

© Sinexcel 2024. All rights reserved.



Everything about profitability and charging experience